

MCMO 1200—Mobile Cook Station



Shown with KRNP & WOPC table top model

TECHNICAL SPECIFICATION

- **Main top:** Pressed stainless steel outer casing incorporating flush apertures to accept standard table top Adventys induction hobs
- **Set down section:** Complete with apertures to accept removable 900mm containers and cylindrical pots (supplied with unit)
- **Standard components:** Unit supplied as standard with 2x KRNP2800 flat top induction hob. Alternative models available on request.
- **Undershelf:** Pressed stainless steel base shelf designed to accept microwave oven or for storage of materials / cutting boards etc.
- **Castors:** Unit mounted on easy glide castors. Two castors to front are lockable to secure unit in position.

Technical Data Sheet

WHY INDUCTION?

- **Safety:** Induction technology heats the cookware, whilst the surrounding area stays cool to touch. Built in safety features include overheat and boil-over sensors, empty pan detector.
- **Precision:** Precise temperature control and instant response. Rotary controls located with remote fitted control panel distributed for perfect and consistent results.
- **Power:** Twice as fast compared to any other cooking method, from 50watts to 3kW. The 280 mm inductor is the largest on the market.
- **Efficiency:** 90% energy efficient, (compared to 50% for gas), high efficiency = maximum yield. Energy consumption half that of gas.
- **Ease of Maintenance:** Surface simply wipes clean after use.
- **Ideal for all types of cooking:** Searing meat, braising, boiling, sauté, shallow fry, stir fry, casseroles, crepes, omelettes, eggs, melting chocolate. From production to pastry areas and great for theatre cooking!

TECHNICAL DETAILS

- **External Dimensions:** 1200mm long x 720mm deep x 900mm high. Unit sized to accept two table top Adventys induction hobs
- **Aperture Dimensions:** 370mm wide x 540mm deep and clear depth of 200mm must be left below the unit. The unit should not be installed above means of heat (hotcupbard / oven / etc). If installed within a closed void adequate ventilation is required. For additional detail please consult installation manual.
- **Power:** 2.8kW per unit - Units fitted as standard with three core 1.5m cable and 13amp plug.
- **Packing:** Unit shipped in box suitable for transportation. Unit has a net weight of 20kgs
- **Standards:** Complies with EN60335-2-36 (European Standard for safety of electrical appliances. IP259 (Protection rating) NFU60-010 (Hygiene)